



Track dumpers



Wheel dumpers



Compact dumpers



Bergmann dumpers.
The models.

Bergmann. Built for you.



Made in Germany.

BERGMANN

Compact dumpers

Fast and manoeuvrable.

With a short tail, high sitting position, economical engine and swivel tip, a compact dumper C805s, C807s and C810s is your transport vehicle for fast and safe work at small and medium-sized construction sites. Equipped with a weather protection roof with a windscreen (optional), the C810s can be used all year round. Well-designed: the roof is simply lowered for transport on a truck.

➤ Best overview

A short tail and a high sitting position ensure the operator the best all-round visibility. For quick and safe work.

➤ Year-round use

Thanks to a collapsible weather protection roof (optional). In focus: health protection, profitability, transport costs.

➤ Safety for the operator

The operator enters the dumper outside the danger area. Because safety is the priority, right from the start.

C 805 s

C 807 s

C 810 s



C805s



C807s



C810s

Wheel dumpers

Masterful at any construction site.

C 815 s

The wheel dumper C815s shows that efficient work, cross-country mobility, travelling comfort and safety are ideally compatible. Any C815s confidently masters everyday challenges. The Bergmann provides the operator with optimal conditions for concentrated work. The rotating operator stand (optional) ensures the best visibility, both forwards and backwards. The interior of the air-conditioned driver's cab inspires with high quality equipment.

➤ Best all-terrain traction

With large tyres, articulated swivel joint and spring-suspension front axle, the C815s also safely handles rough terrain under its wheels.

➤ A real performer

In addition to high performance technology, the features of the C815 enable fast, safe work.

➤ For any requirements

Rear, three-way, swivel tip or carrier vehicle with quick-change apparatus, your Bergmann has the equipment you need for your construction site.



C815s | Three-way tip dumper



C815s | Rear tip dumper



C815s | Swivel tip dumper

Track dumpers

C 912s

Strong in all conditions.

The track dumper C912s does its job even on rough terrain. The powerhouses on tracks convince with high transport performance, are low-emission and economical in fuel consumption and offer maximum safety. Two hydrostatic drive motors with constant full power, optimal weight distribution with any load and the hydraulic parking brake for a guaranteed secure hold even on extreme inclines make practically any terrain accessible.

▶ High speed

With a well-conceived safety concept and a driving speed of up to 9.3 mph, the C912s is convincing even on the most difficult substrate. Safe and high-performance.

▶ Economical and low-emission

State-of-the-art engine technology convinces with low fuel consumption and low emission values. Economical and environmentally friendly.

▶ Convincing ergonomics

The spacious driver's cab with rotating operator stand (optional) makes turning manoeuvres superfluous. Efficient and back-friendly.



C912s | Rear tip dumper



C912s | Swivel tip dumper



C912s | Carrier vehicle

Bergmann dumpers.

The models.

With a comprehensive dumper programme for payloads up to 28 tons, Bergmann offers high-performance, economical transport solutions for all application areas. At the construction site, in the roughest terrain and underground. With competent usage consultation, we assist you in selecting the vehicle that ideally fulfils your requirements.

Type	Compact dumpers						Wheel dumpers						Track dumpers			
	C805s		C807s		C810s		C815s						C912s			
Tilting direction	swivel tip		swivel tip		swivel tip		rear tip		three-way tip		swivel tip		rear tip		swivel tip	
Payload (kg/lb)	4,500	9,921	6,000	13,228	9,000	19,842	12,000	26,455	12,000	26,455	12,000	26,455	10,000	22,046	10,000	22,046
Empty weight (kg/lb)	3,450	7,606	4,300	9,480	6,200	13,669	9,080	20,017	10,020	22,090	11,140	24,559	14,250	31,415	14,850	32,738
Bucket capacity	m ³	yd ³	m ³	yd ³	m ³	yd ³	m ³	yd ³	m ³	yd ³	m ³	yd ³	m ³	yd ³	m ³	yd ³
Struck	1.9	2.5	2.5	3.3	3.6	4.7	5.0	6.5	4.2	5.5	6.3	8.5	4.7	6.1	4.7	6.1
Heaped	2.6	3.4	3.6	4.7	4.6	6.0	8.0	10.5	8.0	10.5	8.0	10.5	6.5	8.5	6.5	8.5
Engine																
Manufacture	Kubota		Cummins		Cummins		Cummins		Cummins		Cummins		Cummins		Cummins	
Power (kW/hp)	53	71.07	55	73.75	75	100.58	119	159.58	119	159.58	119	159.58	180	241.38	180	241.38
Rotational speed (rpm)	1,600		2,200		2,200		2,200		2,200		2,200		2,200		2,200	
Emission standard	Stage 5		Stage 5		Stage 5		Stage 5		Stage 5		Stage 5		Stage 5		Stage 5	
Tire or chain size																
Type	12.5/80-18 MPT		405/70 R20		500/60 R20		20.5-25		20.5-25		20.5-25		750 mm		750 mm	
Drive	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph	km/h	mph
Speed I	0-8	0-5	0-8	0-5	0-9	0-5.6	-	-	-	-	-	-	0-8	0-5	0-8	0-5
Speed II	0-28	0-17.4	0-28	0-17.7	0-28	0-17.4	-	-	-	-	-	-	0-15	0-9.3	0-15	0-9.3
1. gear f/r	-	-	-	-	-	-	6/6	3.7/3.7	6/6	3.7/3.7	6/6	3.7/3.7	-	-	-	-
2. gear f/r	-	-	-	-	-	-	9/15	5.6/9.3	9/15	5.6/9.3	9/15	5.6/9.3	-	-	-	-
3. gear f/r	-	-	-	-	-	-	14/33	8.7/20.5	14/33	8.7/20.5	14/33	8.7/20.5	-	-	-	-
4. gear f	-	-	-	-	-	-	21	13.0	21	13.0	21	13.0	-	-	-	-
5. gear f	-	-	-	-	-	-	32	19.9	32	19.9	32	19.9	-	-	-	-
6. gear f	-	-	-	-	-	-	40	24.9	40	24.9	40	24.9	-	-	-	-
Dimensions																
	mm	ft	mm	ft	mm	ft	mm	ft	mm	ft	mm	ft	mm	ft	mm	ft
Total length	4,256	13.96	4,575	15.01	5,050	16.57	6,834	22.42	7,593	24.91	7,129	23.39	5,963	19.56	6,246	20.49
Total width	1,800	5.91	2,043	6.70	2,420	7.94	2,505	8.22	2,541	8.34	2,500	8.20	2,900	9.51	2,900	9.51
Clearance height																
without beacon light	2,765	9.07	3,087	10.13	3,239	10.63	3,028	9.93	3,028	9.93	3,028	9.93	3,050	10.01	3,050	10.01
Dumping height	979	3.21	1,141	3.74	1,175	3.85	923	3.03	449	1.47	1,441	4.73	797	2.61	1,058	3.47
Ground clearance	305	1.00	326	1.07	313	1.03	429	1.41	429	1.41	424	1.39	613	2.01	613	2.01
Load height (front)	1,479	4.91	1,638	5.37	1,893	6.21	2,110	6.92	2,052	6.73	2,273	7.46	1,646	5.40	1,670	5.48
Turning radius, inner	2,060	6.76	2,892	9.49	3,788	12.43	4,290	14.07	4,610	15.12	4,520	14.83	-	-	-	-
Turning radius, outer	4,025	13.21	5,033	16.51	6,295	20.65	7,100	23.29	7,450	24.44	7,495	24.59	-	-	-	-




C805s | C807s | C810s

compact dumpers | open
swivel tip



C815s

wheel dumpers | cab
rear, three-way or swivel tip



C912s

track dumpers | cab
rear or swivel tip

Ready for the future.

New names. New opportunities. Worldwide.

All Bergmann vehicles have had new names since 2020. With this strategic step, we are adapting our system to the international market and are thus setting the course for further expansion. For you, everything remains the same: Bergmann will continue to stand for first-class quality "Made in Germany".



Bergmann 2060

C 807 s



Bergmann 3012

C 815 s



Bergmann 4010

C 912 s

Bergmann. Built for you.



Made in Germany.

Bergmann Maschinenbau GmbH & Co. KG
Essener Straße 7 | 49716 Meppen | Germany
T +49 (0) 5932 7292-0 | info@bergmann-mb.de
www.bergmann-dumper.de

BERGMANN